



## FCG SERIES FCPRODUCTS MODELS AND SPECIFICATIONS:

Battery Model	Rated Voltage (V)	Rated Capacity (Ah)	Dimension (mm)				Weight (kg±3%)	Terminal		Screw
			L	W	H	Total H.		Type	Position	
FCG12-24	12	24/10HR	165	126	174	174	7.8	T2	B	M6×16
FCG12-26	12	26/10HR	166	175	126	126	8.4	T2	B	M6×16
FCG12-33	12	33/10HR	196	130	155	167	10.1	T3	A	M6×16
FCG12-38	12	38/10HR	198	166	174	174	12.4	T2	B	M6×16
FCG12-50	12	50/10HR	229	138	208	212	15.9	T3	A	M6×16
FCG12-65	12	65/10HR	350	167	178	178	20.6	T3	A	M6×16
FCG12-70	12	70/10HR	260	169	211	215	21.8	T3	A	M6×16
FCG12-90	12	90/10HR	307	169	211	215	26.7	T3	A	M6×16
FCG12-100	12	100/10HR	331	174	214	219	29.2	T4	B	M6×16
FCG12-120	12	120/10HR	407	174	210	233	34.4	T5	A	M6×16
FCG12-150	12	150/10HR	484	171	241	241	43.7	T4	A	M6×16
FCG12-160	12	160/10HR	532	206	215	219	48.5	T4	C	M6×16
FCG12-200	12	200/10HR	522	240	219	224	58.5	T5	C	M6×16
FCG12-220	12	220/10HR	520	269	203	207	68.3	T5	C	M6×16
FCG12-250	12	250/10HR	520	268	220	225	70.3	T5	C	M6×16